

Naperville CUSD 203 - Switch Bill of Materials

Vendor Name						
Active Spin# (required)						
Part Number	Description	Unit Cost	Quantity	Cost	Amount Erate Eligible (See Note 1)	Amount Erate Ineligible
EX4400-48MP						
EX4400-48MP	12x1/2.5/5/10G, 36x1/2.5G Multigigabit switch with 2x100G uplink/stacking ports. 90W POE. MACsec AES256. Optional extension module:4x10G or 4x25G		30			\$ -
EX4400-EM-4S	4x10G SFP+ extension module for EX4400 series of switches		30			\$ -
SUB-EX48-1S-5Y-COR	5 Year Wired Assurance Subscription for EX48 port switches including JTAC Support; Juniper Care Core Support for EX2300, EX3400, EX4300, EX4400 24 ports devices.		30			\$ -
EX4400-48P						
EX4400-48P	48x1G POE switch with 2x100G uplink/stacking ports. 90W POE. MACsec AES256 capable (optional license sold separately). Optional extension module(sold separately): 4x10G or 4x25G		54			\$ -
EX4400-EM-4Y	4x25G SFP28 extension module for EX4400 series of switches. MACsec AES256		2			\$ -
SUB-EX48-1S-5Y-COR	5 Year Wired Assurance Subscription for EX48 port switches including JTAC Support; Juniper Care Core Support for EX2300, EX3400, EX4300, EX4400 24 ports devices.		54			\$ -
EX4650-48Y-AFO						
EX4650-48Y-AFO	EX4650 48x25G+8x100G 1U AC port side intake and PSU side exhaust		2			\$ -
SUB-EX48-1S-5Y-46N	5 Year Wired Assurance Subscription for EX4600 Series Switches including Next Day Support; Juniper Care Next Day Support for EX4600series all models.		2			\$ -
EX2300-24MP						
EX2300-24MP	EX2300 class multi-gig switch with 16 x 1G, 8 x 1G/2.5G copper ports, 30w PoE		1			\$ -

SUB-EX24-1S-5Y-COR	5 Year Wired Assurance Subscription for EX24 port switches including JTAC Support; Juniper Care Core Support for EX2300, EX3400, EX4300, EX4400 24 ports devices.		1			\$ -
Additional Items						
JNP-100G-DAC-1M	QSFP28, 100GE Direct Attach Copper Cable, 1 meter, Standard Temperature (0 through 70 DEGREE C), 0.015W, 30 AWG		86			\$ -
SFP-25G-SR-C	SFP28, 25GBASE-SR, MMF OM3 70 meters and OM4 100 meters, Standard Temperature (0 through 70 DEGREE C), Duplex LC connector		4			\$ -
SFPP-10G-SR-C	SFP+, 10GBASE-SR, MMF OM3 300 meters and OM4 400 meters, Standard Temperature (0 through 70 DEGREE C), Duplex LC connector		32			\$ -
		Equipment/License/Support:		\$ -	\$ -	\$ -
		Other Cost:		\$ -	\$ -	\$ -
		Shipping:		\$ -	\$ -	\$ -
		Totals		\$ -	\$ -	\$ -

NOTES

- Vendor shall list eligible portion of cost in "Amount E-rate Eligible" column. Formulas will calculate the remaining ineligible cost. If the "Amount E-rate Eligible" column is left blank, all costs will be incorrectly listed as ineligible. Verify all calculations.

EVALUATION CRITERIA

- Price of E-rate Eligible Products and Services - 40%
- Price of Ineligible Products and Services – 10%
- Compatibility with Existing Equipment – 20%
- Technical Features – 15%
- District's experience with Vendor– 10%
- Completeness of Proposal – 5%

CRITERIA FOR DISQUALIFICATION OF PROPOSAL

- Generic hardware purchase list provided, without identifying the specific solution to meet the requirements of this RFP
- Proposal does not address specific hardware requirements of this 470
- Proposal does not provide technical feature information
- Incomplete Proposal